

TOTAL FLOOR CARE LTD

Dalsouple Cleaning & Maintenance Programme

Dalsouple have nominated Total Floor Care Ltd as their Service Partner to offer a nationwide cleaning and maintenance service. After the floor has been installed it should be swept clean. Any excess adhesive should be removed by the flooring contractor. **No wet cleaning should take place for 7 days, until the adhesive has fully cured (in accordance with the adhesive manufacturer's instructions).**

Preparation

Product: PRO 1 Heavy Duty Stripper

PRO 1 diluted with 1:10 cold water. Apply the solution sparingly to the floor surface – do not allow it to dry out. Allow 5 minutes contact time. Scrub with standard speed machine fitted with stripping grade pad or brush for higher profile textures. Remove slurry with a wet pickup, damp mop with water; allow the floor to dry thoroughly.

Protection

Product: PRO 2 Protection Undercoat

PRO 3 Emulsion Floor Dressing

Important No one should be allowed on the floor between preparation and protection stages.

PRO 2 Apply neat. An applicator must be used to apply the undercoat. Apply in one direction only; allow polish to dry thoroughly. Apply second coat at right angles to the first, allowing each coat to dry. Should a high gloss finish be required then apply 2 coats of PRO 3 Emulsion floor dressing, allowing each coat to dry.

Maintenance

Product: PRO 4 Maintainer/Floor Finish

The floor should always be dust mopped prior to the following procedures, and spots/stains should be removed with a cloth using undiluted PRO 4.

Damp Mop using PRO 4 diluted 1:50 with water. An applicator must be used to apply the coats of maintainer. Allow to dry.

Spray Cleaning (for smooth finishes such as 'Uni, Marbre, Terrazzo & Granita') use PRO 4 diluted 1:6 with cold water, spray a fine mist over a manageable area 2-3 m², use a buffing grade pad with a suitable high-speed machine until the floor is completely dry. Certain profiled textures may require the use of a cylindrical brush-scrubbing machine such as Nilfisk Advance CA340.

Long Term Maintenance

A long term maintenance programme can be provided by Total Floor Care Ltd upon request.

Wet Areas

External ramps/changing rooms etc. should be treated with PRO 1 as above, then cleaned with PRO 1 diluted 1:200 with cold water, allow the floor to dry.

Vertical Application

Product: SIL As per instructions, do not allow to come into contact with the floors (separate data sheet available).

Raised Access Floors _Separate data sheet available.

Dalsport, Dalkit, Dal-equipe. _Loose lay interlocking tiles

Product: PRO 1 Heavy Duty Stripper

PRO 1 diluted 1:10 with cold water. Apply the solution sparingly to the floor surface – do not allow it to dry out. Allow 5 minutes contact time. Use a cylindrical brush-scrubbing machine (if appropriate machinery is not available the floor can be damp mopped). Remove slurry with a wet pickup, damp mop with water; allow the floor to dry thoroughly. This procedure may need to be repeated if the waxy film (release agent from the manufacturing process) on the surface of the product is still present.

Maintenance

Product: PRO 1 Heavy Duty Stripper

Clean the floor with PRO 1 diluted 1:200 with cold water, if appropriate machinery is not available the floor can be damp mopped, then allow to dry.

Tel: 01278 652150

Fax: 01278 653846

3 School Lane Combwich Somerset TA5 2QS

Company Reg No. 4125508

VAT Reg No. 741 5931 32

E-Mail: info@totalfloorcare.com