

Cleaning and Maintenance Information

Accessories

HD2 Stair Edging

Data Sheet: (sheet 1 of 1) 04/03/08

This leaflet has been compiled to help the user obtain optimum performance and satisfaction from their selected product:

Preventative Maintenance Programme

A regular scheduled maintenance programme should be employed to prevent the build up of dirt and grease, which will reduce the slip-resistant properties of the channel and detract from the overall appearance of the product.

NB. Under no circumstances should degreasers of any type and floor cleaners/ sanitizers containing hydrocarbons or citrus based agents be used to clean any Gradus Stair Edging. Steam cleaners, power washers, floor sealants, polishes or any coatings should not under any circumstances be used on inserts.

Daily Cleaning

Brush down the channel using a soft bristled brush and remove dust particles from the insert by wiping with a damp cloth.

Aluminium Channel

Stubborn marks such as boot blacking may be removed from the aluminium channel by means of a green scotch pad and neutral detergent. Light surface scratches can be removed with careful use of fine wire wool and buffed with a soft cloth.

Interior standard, Interior grained and Exterior Inserts Twice Weekly or as Required

Brush down the channel using a soft bristled brush. With clean, warm water, containing the correct dilution ratio of ph neutral cleaning solution apply a small amount to a wet green scotch pad and gently clean the surface of the insert in a left to right motion. During the clean, the water must be changed on a regular basis. **Do not** soak the insert. Once the stair edging has been cleaned thoroughly rinse with fresh, clean water and dry with a dry lint free cloth.

On completion the staircase should not be used until completely dry.

Xtra-grip and Xtra-grip Plus Inserts Twice Weekly or as Required

Brush down the channel using a soft bristled brush. With clean, warm water, containing the correct dilution ratio of ph neutral cleaning solution, gently clean the surface of the insert in a left to right motion using a scrubbing brush. During the clean, the water must be changed on a regular basis. **Do not** soak the insert. Once the stair edging has been cleaned thoroughly rinse with fresh, clean water and dry with a dry lint free cloth.

On completion the staircase should not be used until completely dry.