



- Polyflor Expona Design PU incorporates a polyurethane surface treatment, which protects the floorcovering by resisting soiling and scuffing. This protection facilitates a reduction in the intensity of the construction clean and provides the foundation for the ongoing maintenance regime. This easier cleanability offers maintenance cost savings when compared with non-treated materials.
- The following maintenance instructions are designed to minimise the cost factor, without compromising the long-term appearance of your floorcovering.

**INITIAL CONSTRUCTION CLEAN**

- Remove all loose debris.
- Ensure that all traces of adhesive are removed from the surface of the floorcovering.
- Mop sweep or vacuum to remove dust and grit.
- Damp mop with a neutral detergent.
- If required, dry buff with a 1000 rpm plus rotary machine fitted with a suitable clean pad.

**ROUTINE MAINTENANCE**

- The following recommendations are provided as a guideline, and the frequencies can be changed to optimise the appearance.

DAILY

- Mop sweep or vacuum to remove dust and loose dirt.
- If required, spot clean to remove stubborn marks with a neutral cleanser.
- If required, dry buff to restore finish.

WEEKLY/MONTHLY

- Assess the appearance of the floor.
- If required, scrub with a scrubber dryer fitted with suitable pads, and using neutral cleanser (pH 7 to 9).
- If required, dry buff to restore finish.

**APPLICATION OF A FLOOR DRESSING**

- Should you wish to apply a floor dressing to the floorcovering to provide extra protection in heavily trafficked areas, please follow details of the procedure below.
- Using an applicator and tray, or Kentucky mop with wringer and bucket, the first coat should be applied thinly and evenly across the floor, to within 200mm of the skirtings. It should then be left to dry. This normally takes approximately thirty minutes, depending on the ambient conditions and the thickness of the coating.
- When the first coat is dry, a second coat should be applied at right angles to the direction of the first. Subsequent coats should be applied at right angles, and the final coat should be applied right up to the skirting.
- Two to three thin coats are usually sufficient to provide excellent resistance to abrasion, scuffing and removal of black heel marking. However, be guided by your own periodic assessments for the particular location.
- In order to minimise costs, subsequent polish applications may be applied only to traffic paths.
- Periodically - generally every six months - assess the appearance of the floor. If there is an unacceptable build-up of polish, this should be stripped and reapplied, as per the instructions above.



NOTE: The maintenance regime requires the installation of an effective barrier matting system.

- Cleaners and detergents should be diluted as per the manufacturers' instructions. These maintenance instructions are intended for Polyflor Expona Design PU, which incorporates a polyurethane surface treatment. For other Polyflor products, reference should be made to their specific floorcare sheets.
 - For further information and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. Always follow the Health and Safety guidance provided.
 - At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.
- REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.**

expona[®] DESIGN



FLOORCARE

APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

MAINTENANCE PRODUCTS

PRODUCT	DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com	BRITISH NOVA Tel: 01295 254030	PROCHEM Tel: 0208 974 1515 www.prochem.co.uk	EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk	ECOLAB LTD Tel: 01793 511221 www.ecolab.com	JOHNSON/DIVERSEY Tel: 01604 783500 www.johnsondiversey.co.uk	SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk
NEUTRAL CLEANSER	Active Cleaner	Liquid 99	Prodet	High Class	Brial Action Plus	Taski 300 Carefree Stride 1000	Neutra scrubber dryer detergent
ALKALINE CLEANSER		Novaways Novaways Multi Purpose Sanitiser	Alkleen Ultrapac Renovate Powerclean	E.M.C Versatile Lift	Gloss Express Imi Orange Imi Top Powerclean Imi Action Plus	Brillo Cleaner/Degreaser Carefree Stride 2000 Sprint Hard Surface Cleaner Aggressor	HD Degreaser Triple Selcien Multi Purpose Cleaner
GERMICIDAL CLEANSER		Novacross Non food areas Novacross (unperfumed) Food areas	Protect	Final Touch Esteem Lift	Bioscan	Lifeguard Cleaner/Disinfectant Conc. Shield Lifeguard cleaner Disinfectant Trigger	Selguard Selgeine
MAINTAINER/WASH & WAX	Floor Cleaner R1000	Novacare Novacare Lime-lite	Protreat	Easy Shine Clean & Shine Easy Shine	Formula 71 Indur Brillant Plus Spirit Restorer Indur Top	Carefree Maintainer Carefree Mop & Shine Carefree Stride 3000 Taski Tensol	Selsheen Minit Glass Fast Lane
DRY BRIGHT EMULSION POLISH	Floor Shine	Nova Long Life Nova Long Life Satin Finish	Proshine	Sustain Mexepol Enhance	Isi Star Phazer Isi Star Lodan Star Phazer Lodan Star Tuklar Medical	Carefree Satin Carefree Eturnum Carefree Emulsion	Selbrite Diamond Bright
SEMI BUFFABLE EMULSION POLISH	Floor Mat	Nova Supercote		Ovacryl		Carefree Buffable Floor Polish	Selxel Seldur
FULLY BUFFABLE EMULSION POLISH		Nova Superphalte		Easy Shine	Gemstar Laser Phazer Gem Star Laser		Selgio
POLISH STRIPPER	Clean & Strip	Nova Starbrite Nova 2001	Prostrip	Easystrip Sure Strip	Benduroil Maxx Benduroil Top Strip	Carefree Stripper Carefree Speed Stripper	Selate Selspeed
POWER CLEANER (Spot Cleaner)	Turbo Strip	Cleanol Lift		Lift		Sprint Spitfire	

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary.

For the latest information, please check our web site at www.polyflor.com

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING



POLYFLORTM
COVERING THE WORLD