



- For light soiling wipe the walls with a damp cloth, using a neutral cleanser diluted to the manufacturer's instructions.
- For heavy cleaning, use an alkaline cleanser diluted to the manufacturer's instructions. For stubborn marks use a deck scrubber, scrubbing brush or doodle bug. Wipe the walls with a damp cloth, using clean water and a small amount of neutralising agent such as acetic acid.



- Under most circumstances, the wall will not require a sealer coat of polish. If, however, it is felt necessary to either provide a protective finish or minimise maintenance, a matt finish metallised polish should be applied.
- Using a damp cloth the polish should be applied to a previously cleaned surface, as described in the previous section, in an even coat. Do not over-apply, to avoid runs in the polish.



- The frequency is dependent upon the rate of soiling.
- If lightly soiled wipe the walls with a damp cloth, using a neutral cleanser diluted to the manufacturer's instructions.
- If heavily soiled, especially with grease, wipe the walls with a damp cloth, using an alkaline cleanser diluted to the manufacturer's instructions. Afterwards rinse the walls, using clean warm water and a small amount of neutralising agent such as acetic acid.



- Should the dressing have to be removed a polish stripper, diluted to the manufacturer's instructions, should be applied to a small section at a time, using a wet cloth. The stripping solution should be left on the wall for almost 10 minutes and the surface should then be agitated using a deck scrubber, scrubbing brush, or doodle bug which has been pre-wetted in the solution.
- Once complete, the walls should be rinsed using a damp cloth and warm water and a small amount of neutralising agent such as acetic acid.
- Once the whole room has been stripped, a new coat of polish can be applied as described above.
- **DO NOT USE STRONG KITCHEN DEGREASERS ON VINYL SURFACES.**



- Always follow the Health and Safety guidance provided.
 - At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.
 - Cleaners and detergents should be diluted as per the manufacturers' instructions. For recommended products, see the Polyflor Approved Maintenance Products sheet located within the Technical section of www.polyflor.com.
- REGULAR CLEANING IS MORE BENEFICIAL TO THE WALLCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.**
- For further information and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR
POLYCLAD P
POLYCLAD PLUS P

WALL CLADDING

WALLCARE